



AVIT
AARUPADAI VEEDU INSTITUTE OF TECHNOLOGY



VINAYAKA MISSION'S
RESEARCH FOUNDATION
(Deemed to Be University under section 3 of the UGC Act 1956)



Accredited by NAAC



Approved by AICTE

DEPARTMENT OF MECHANICAL ENGINEERING

34421C05-FLUID MECHANICS AND MACHINERY

LAB MANUAL

Prepared by

S.ASHOKKUMAR, M.E., (PHD)

A.ELANTHIRAIYAN, M.E., (PHD)

ASSITANT PROFESSOR (G-II) /MECH

ASSITANT PROFESSOR (G-II) /MECH

A LIST OF BASIC SAFETY RULES

1. Students should wear durable clothing that covers the arms, legs, torso and feet. (Note: sandals, shorts, tank tops etc. have no place in the lab. Students inappropriately dressed for lab, at the instructors discretion, be denied access)
2. To protect clothing from chemical damage or other dirt, wear a lab apron or lab coat. Long hair should be tied back to keep it from coming into contact with lab chemicals or flames.
3. In case of injury (cut, burn, fire etc.) notify the instructor immediately.
4. In case of a fire or imminently dangerous situation, notify everyone who may be affected immediately; be sure the lab instructor is also notified.
5. In case of a serious cut, stop blood flow using direct pressure using a clean towel, notify the lab instructor immediately.
6. Eating, drinking and smoking are prohibited in the laboratory at all times.
7. Never work in the laboratory without proper supervision by an instructor.
8. Never carry out unauthorized experiments. Come to the laboratory prepared. If you are unsure about what to do, please ask the instructor.

LABARATORY CLASSES - INSTRUCTIONS TO STUDENTS

1. Students must attend the lab classes with ID cards and in the prescribed uniform.
2. Boys-shirts tucked in and wearing closed leather shoes. Girls" students with cut shoes, overcoat, and plait incite the coat. Girls" students should not wear loose garments.
3. Students must check if the components, instruments and machinery are in working condition before setting up the experiment.
4. Power supply to the experimental set up/ equipment/ machine must be switched on only after the faculty checks and gives approval for doing the experiment. Students must start to the experiment. Students must start doing the experiments only after getting permissions from the faculty.
5. Any damage to any of the equipment/instrument/machine caused due to carelessness, the cost will be fully recovered from the individual (or) group of students.
6. Students may contact the lab in charge immediately for any unexpected incidents and emergency.
7. The apparatus used for the experiments must be cleaned and returned to the technicians, safely without any damage.
8. Make sure, while leaving the lab after the stipulated time, that all the power connections are switched off.

9. EVALUATIONS:

All students should go through the lab manual for the experiment to be carried out for that day and come fully prepared to complete the experiment within the prescribed periods. Student should complete the lab record work within the prescribed periods.

Students must be fully aware of the core competencies to be gained by doing experiment/exercise/programs.

Students should complete the lab record work within the prescribed periods.

The following aspects will be assessed during every exercise, in every lab class and marks will be awarded accordingly:

Preparedness, conducting experiment, observation, calculation, results, record presentation, basic understanding and answering for viva questions.

In case of repetition/redo, 25% of marks to be reduced for the respective component.

NOTE 1

Preparation means coming to the lab classes with neatly drawn circuit diagram /experimental setup /written programs /flowchart, tabular columns, formula, model graphs etc in the observation notebook and must know the step by step procedure to conduct the experiment.

Conducting experiment means making connection, preparing the experimental setup without any mistakes at the time of reporting to the faculty.

Observation means taking correct readings in the proper order and tabulating the readings in the tabular columns.

Calculation means calculating the required parameters using the approximate formula and readings.

Result means correct value of the required parameters and getting the correct shape of the characteristics at the time of reporting of the faculty.

Viva voce means answering all the questions given in the manual pertaining to the experiments.

Full marks will be awarded if the students performs well in each case of the above component

NOTE 2

Incompletion or repeat of experiments means not getting the correct value of the required parameters and not getting the correct shape of the characteristics of the first attempt. In such cases, it will be marked as **“IC” in the red ink** in the status column of the mark allocation table given at the end of every experiment. The students are expected to repeat the incomplete the experiment before coming to the next lab. Otherwise the marks for IC component will be reduced to **zero**.

NOTE 3

Absenteeism due to genuine reasons will be considered for doing the **missed experiments**.

In case of power failure, extra classes will be arranged for doing those experiments only and assessment of all other components preparedness; viva voce etc. will be completed in the regular class itself.

NOTE 4

The end semester practical internal assessment marks will be based on the average of all the experiments.

34421C05 - FLUID MECHANICS AND MACHINERY PRACTICALS

LIST OF EXPERIMENTS

Exp No.	NAME OF THE EXPERIMENT
1.	Determination of co-efficient of discharge for orifice meter
2.	Determination of co-efficient of discharge for venturimeter
3.	Determination of friction factor for a given set of pipes.
4.	Conducting experiments and drawing the characteristic curves of Cent Pump
5.	Conducting experiments and drawing the characteristic curves of Reciprocating Pump
6.	Conducting experiments and drawing the characteristic curves of Gear
7.	Conducting experiments and drawing the characteristic curves of Jet P
8.	Conducting experiments and drawing the characteristic curves of Kap Turbine
9.	Study about the performance characteristics curves of Pelton wheel
10.	Study about the performance characteristics curves of Francis Turbine

DETERMINATION OF THE CO-EFFICIENT OF DISCHARGE OF GIVEN ORIFICE METER

AIM:

To determine the co-efficient discharge through orifice meter

APPARATUS REQUIRED:

1. Orifice meter
2. Differential U tube manometer
3. Collecting tank
4. Stop watch
5. Scale

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{act} = A \times h / t \text{ (m}^3 / \text{s)}$$

2. THEORETICAL DISCHARGE:

$$Q_{th} = a_1 \times a_2 \times \sqrt{2gh} / \sqrt{a_1^2 - a_2^2} \text{ (m}^3 / \text{s)}$$

Where:

- A = Area of collecting tank in m^2
h = Height of collected water in tank = 10 cm
 a_1 = Area of inlet pipe in, m^2
 a_2 = Area of the throat in m^2
g = Specify gravity in m / s^2
t = Time taken for h cm rise of water
H = Orifice head in terms of flowing liquid
= $(H_1 \sim H_2) (s_m / s_1 - 1)$

Where:

- H1 = Manometric head in first limb
H2 = Manometric head in second limb
 s_m = Specific gravity of Manometric liquid
(i.e.) Liquid mercury Hg = 13.6
 s_1 = Specific gravity of flowing liquid water = 1

3. CO EFFICIENT OF DISCHARGE:

Co- efficient of discharge = Q_{act} / Q_{th} (no units)

DESCRIPTION:

Orifice meter has two sections. First one is of area a_1 , and second one of area a_2 , it does not have throat like venturimeter but a small holes on a plate fixed along the diameter of pipe. The mercury level should not fluctuate because it would come out of manometer.

PROCEDURE:

1. The pipe is selected for doing experiments
2. The motor is switched on, as a result water will flow
3. According to the flow, the mercury level fluctuates in the U-tube manometer
4. The reading of H_1 and H_2 are noted
5. The time taken for 10 cm rise of water in the collecting tank is noted
6. The experiment is repeated for various flow in the same pipe
7. The co-efficient of discharge is calculated

MODEL CALCULATION:

RESULT:

The coefficient of discharge through orifice meter is (No unit)

VIVA QUESTIONS

1. For which one, the coefficient of discharge is smaller, venturimeter or Orificemeter?
2. What is the reason for smaller value of C_d ?
3. What is Orifice meter?
4. What is the principle of Orifice meter?
- 5 For discharge measurement through pipes which is having cheaper arrangement and whose installation requires a smaller length?
6. What are the parts of Orifice meter?
7. What is the diameter of the orifice?
8. Where two pressure taps are provided?
9. Where upstream pressure tap is located?

DETERMINATION OF THE COEFFICIENT OF DISCHARGE OF GIVEN VENTURIMETER

AIM:

To determine the coefficient of discharge for liquid flowing through venturimeter.

APPARATUS REQUIRED:

1. Venturimeter
2. Stop watch
3. Collecting tank
4. Differential U-tube
5. Manometer
6. Scale

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{act} = A \times h / t \quad (\text{m}^3 / \text{s})$$

2. THEORETICAL DISCHARGE:

$$Q_{th} = a_1 \times a_2 \times \sqrt{2gh} / \sqrt{a_1^2 - a_2^2} \quad (\text{m}^3 / \text{s})$$

Where:

- A = Area of collecting tank in m^2
h = Height of collected water in tank = 10 cm
 a_1 = Area of inlet pipe in m^2
 a_2 = Area of the throat in m^2
g = Specific gravity in m / s^2
t = Time taken for h cm rise of water
H = Orifice head in terms of flowing liquid
= $(H_1 - H_2) (s_m / s_1 - 1)$

Where:

- H1 = Manometric head in first limb
H2 = Manometric head in second limb
 s_m = Specific gravity of Manometric liquid
(i.e.) Liquid mercury Hg = 13.6
 s_1 = Specific gravity of flowing liquid water = 1

3. CO EFFICIENT OF DISCHARGE:

$$\text{Co- efficient of discharge} = Q_{\text{act}} / Q_{\text{th}} \quad (\text{no units})$$

DESCRIPTION:

Venturimeter has two sections. One divergent area and the other throat area. The former is represented as a_1 and the later is a_2 water or any other liquid flows through the Venturimeter and it passes to the throat area the value of discharge is same at a_1 and a_2 .

PROCEDURE:

1. The pipe is selected for doing experiments
2. The motor is switched on, as a result water will flow
3. According to the flow, the mercury level fluctuates in the U-tube manometer
4. The reading of H_1 and H_2 are noted
5. The time taken for 10 cm rise of water in the collecting tank is noted
6. The experiment is repeated for various flow in the same pipe
7. The co-efficient of discharge is calculated

MODEL CALCULATION:

RESULT:

The co efficient of discharge through Venturimeter is (No unit)

VIVA QUESTIONS

1. What is cavitation?
2. What is value of diameter of throat?
3. What should be done to avoid cavitation?
4. Write the formula for actual discharge.
5. Venturi meter based on which principles?
6. What is Venturi meter? And what is its use?
7. Which part is smaller, convergent cone or divergent cone? Why?
8. Where separation of flow occurs?
9. Which portion is not used for discharge measurement?
10. Which cross-sectional area is smaller than cross sectional area of inlet section?
11. Where velocity of flow greater?
12. Where pressure is low in Venturi meter?
13. How pressure difference is determined?
14. Between which sections the pressure difference can be determined? Inlet section and Throat

Determination of friction factor for a given set of pipes.

AIM

To determine the friction factor for the given pipe

APPARATUS REQUIRED

1. A pipe provided with inlet and outlet and pressure tapping
2. Differential U-tube manometer
3. Collecting tank with piezometer
4. Stopwatch
5. Scale

THEORY

A pipe is a closed conduit which is used for carry fluid under pressure. Pipes are commonly circular in section and the liquid flowing in a pipe is always subjected to resistance due to shear forces between fluid particles and the boundary walls of the pipes and between the fluid particles themselves results from viscosity of the fluid. The resistance to the flow of liquid is known as frictional resistance. Due to this thick fluid will always have some loss of energy in the direction of flow. Head loss due to friction can be computed by Darcy- Weisbach equation.

FORMULAE

1. FRICTION FACTOR (F):

$$f = \frac{2 g d h_f}{4 l v^2}$$

Where, g = Acceleration due to gravity (m / sec²)

d = Diameter of the pipe (m)

l = Length of the pipe (m)

v = Velocity of liquid following in the pipe (m / s) = Q/a

h_f = Loss of head due to friction (m) = $h_1 - h_2$

Where h_1 = Manometric head in the first limbs

h_2 = Manometric head in the second limbs

2. ACTUAL DISCHARGE:

$Q = A \times h / t$ (m³ / sec)

Where A = Area of the collecting tank (m²)

h = Rise of water for 10 cm (m)

t = Time taken for 10 cm rise (sec)

PROCEDURE:

1. The diameter of the pipe is measured and the internal dimensions of the collecting tank and the length of the pipe line is measured.
2. Keeping the outlet valve closed and the inlet valve opened
3. The outlet valve is slightly opened and the manometer head on the limbs h1 and h2 are noted
4. The above procedure is repeated by gradually increasing the flow rate and then the corresponding readings are noted

Model calculation

Result :

The frictional factor 'f' for given pipe = x 10⁻² (no unit)

VIVA QUESTIONS :

1. Define Boundary layer Thickness.
2. List the various types of boundary layer thickness.
3. Define displacement thickness.
4. Define momentum thickness
5. Define energy thickness
6. What is meant by energy loss in a pipe?
7. Explain the major losses in a pipe.
8. Explain minor losses in a pipe.
9. State Darcy-Weisbach equation.
10. What is the expression for head loss due to friction?

Conducting experiments and drawing the characteristic curves of Centrifugal Pump

AIM:

To study the performance characteristics of a centrifugal pump and to determine the characteristic with maximum efficiency.

APPARATUS REQUIRED:

1. Centrifugal pump setup
2. Meter scale
3. Stop watch

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{act} = A \times y / t \quad (\text{m}^3 / \text{s})$$

Where:

A = Area of the collecting tank (m^2)

y = 10 cm rise of water level in the collecting tank

t = Time taken for 10 cm rise of water level in collecting tank.

2. TOTAL HEAD:

$$H = H_d + H_s + Z$$

Where:

H_d = Discharge head, meter

H_s = Suction head, meter

Z = Datum head, meter

3. INPUT POWER:

$$I/P = (3600 \times N \times 1000) / (E \times T) \text{ (watts)}$$

Where:

N = Number of revolutions of energy meter disc

E = Energy meter constant $(\text{rev} / \text{Kw hr})$

T = time taken for 'Nr' revolutions (seconds)

OBSERVATION :

TABULATION :

S.No	Suction gauge Hs m of water	Suction head Hs m of water	Delivery Gauge Reading (hd) m of water	Delivery Head (Hd) m of water	Total Head (H) m of water	Time taken for „h“ rise of water (t) S	Time taken for Nr revolutio n t S	Actual Discharge (Qact) x10 ⁻³ m ³ \sec	Input Power (Pi) watt	Output Power (Po) watt	% η
Average =											

4. OUTPUT POWER:

$$P_o = \rho \times g \times Q \times H / 1000 \quad (\text{watts})$$

Where,

$$\rho = \text{Density of water} \quad (\text{kg} / \text{m}^3)$$

$$g = \text{Acceleration due to gravity} \quad (\text{m} / \text{s}^2)$$

$$H = \text{Total head of water} \quad (\text{m})$$

5. EFFICIENCY:

$$\eta_o = (\text{Output power o/p} / \text{input power I/p}) \times 100 \%$$

Where,

$$O/p = \text{Output power kW}$$

$$I/p = \text{Input power} \quad \text{kW}$$

DESCRIPTION:

PRIMING:

The operation of filling water in the suction pipe casing and a portion delivery pipe for the removal of air before starting is called priming.

After priming the impeller is rotated by a prime mover. The rotating vane gives a centrifugal head to the pump. When the pump attains a constant speed, the delivery valve is gradually opened. The water flows in a radially outward direction. Then, it leaves the vanes at the outer circumference with a high velocity and pressure. Now kinetic energy is gradually converted in to pressure energy. The high-pressure water is through the delivery pipe to the required height.

PROCEDURE:

1. Prime the pump close the delivery valve and switch on the unit
2. Open the delivery valve and maintain the required delivery head
3. Note down the reading and note the corresponding suction head reading
4. Close the drain valve and note down the time taken for 10 cm rise of water level in collecting tank
5. Measure the area of collecting tank
6. For different delivery tubes, repeat the experiment
7. For every set reading note down the time taken for 5 revolutions of energy meter disc.

GRAPHS:

1. Actual discharge Vs Total head
2. Actual discharge Vs Efficiency
3. Actual discharge Vs Input power
4. Actual discharge Vs Output power

MODEL CALCULATION:

RESULT:

Thus the performance characteristics of centrifugal pump was studied and the maximum efficiency was found to be _____

VIVA QUESTIONS

1. Define Centrifugal pump.
2. Define Specific speed of a centrifugal pump.
- 3 Efficiencies of a Centrifugal Pump:
4. Centrifugal Pump Mechanical Efficiency:
5. Centrifugal Pump Overall Efficiency:
6. Define Priming of a centrifugal pump.

Conducting experiments and drawing the characteristic curves of Reciprocating Pump

AIM:

To study the performance characteristics of a centrifugal pump and to determine the characteristic with maximum efficiency.

APPARATUS REQUIRED:

1. Reciprocating pump setup
2. Meter scale
3. Stop watch

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{\text{act}} = A \times y / t \quad (\text{m}^3 / \text{s})$$

Where:

A = Area of the collecting tank (m²)

y = 10 cm rise of water level in the collecting tank

t = Time taken for 10 cm rise of water level in collecting tank.

2. TOTAL HEAD:

$$H = H_d + H_s + Z$$

Where:

H_d = Discharge head, meter

H_s = Suction head, meter

Z = Datum head, meter

3. INPUT POWER:

$$I/P = (3600 \times N \times 1000) / (E \times T) \text{ (watts)}$$

Where:

N = Number of revolutions of energy meter disc

E = Energy meter constant (rev / Kw hr)

T = time taken for 'Nr' revolutions (seconds)

Observation: Energy meter constant = 100 rev/kWh : stroke length (L)= 0.045m : bore = 0.04m : piston area (A)= 0.001256637m³ : speed of the pump(N) = 326 rpm
 $Q_{th} = 2LAN/60 \text{ m}^3/\text{s}$

TABULATION :

S.No	Suction gauge Hs m of water	Suction head Hs m of water	Delivery Gauge Reading (hd) m of water	Delivery Head (Hd) m of water	Total Head (H) m of water	Time taken for „h“ rise of water (t) S	Time taken for Nr revolutio n t S	Actual Discharge (Qact) x10 ⁻³ m ³ /sec	Input Power (Pi) watt	Output Power (Po) watt	% η
Average =											

4. OUTPUT POWER:

$$P_o = \rho \times g \times Q \times H / 1000 \quad (\text{watts})$$

Where,

$$\rho = \text{Density of water} \quad (\text{kg} / \text{m}^3)$$

$$g = \text{Acceleration due to gravity} \quad (\text{m} / \text{s}^2)$$

$$H = \text{Total head of water} \quad (\text{m})$$

5. EFFICIENCY:

$$\eta_o = (\text{Output power o/p} / \text{input power I/p}) \times 100 \%$$

Where,

$$O/p = \text{Output power kW}$$

$$I/p = \text{Input power} \quad \text{kW}$$

DESCRIPTION:

Reciprocating pump is a positive displacement pump. A piston reciprocates in a stationary cylinder alternatively drawing in and pushing out the liquid through valves. Mechanical energy supplied to the pump will be converted into hydraulic energy

PROCEDURE:

1. Keep the delivery valve open and switch on the pump.
2. Slowly close the delivery valve and maintain a constant head
3. Note down the suction and delivery gauge reading
4. Note the time taken for h cm rise of water level and n rev of energy meter disc
5. Repeat the experiment for various opening settings of delivery valve

GRAPHS:

1. Actual discharge Vs Total head
2. Actual discharge Vs Efficiency
3. Actual discharge Vs Input power
4. Actual discharge Vs Output power

MODEL CALCULATION:

RESULT:

Thus the performance characteristics of reciprocating pump was studied and the maximum efficiency was found to be _____

CONDUCTING EXPERIMENTS AND DRAWING THE CHARACTERISTICS CURVES OF GEAR PUMP

AIM:

To draw the characteristics curves of gear pump and also to determine efficiency of given gear oil pump.

APPARATUS REQUIRED:

1. Gear oil pump setup
2. Meter scale
3. Stop watch

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{act} = A \times y / t \quad (m^3 / sec)$$

Where,

$$A = \text{Area of the collecting tank} \quad (m^2)$$

$$y = \text{Rise of oil level in collecting tank} \quad (cm)$$

$$t = \text{Time taken for 'h' rise of oil in collecting tank} \quad (s)$$

2. TOTAL HEAD:

$$H = H_d + H_s + Z$$

Where

$$H_d = \text{Discharge head; } H_d = P_d \times 12.5, \quad m$$

$$H_s = \text{Suction head; } P_d = P_s \times 0.0136, \quad m$$

$$Z = \text{Datum head,} \quad m$$

$$P_d = \text{Pressure gauge reading,} \quad kg / cm^2$$

$$P_s = \text{Suction pressure gauge reading, mm of Hg}$$

3. INPUT POWER:

$$P_i = (3600 \times N) / (E \times T) \quad (kw)$$

Where,

$$N_r = \text{Number of revolutions of energy meter disc}$$

$$N_e = \text{Energy meter constant} \quad (rev / Kw hr)$$

$$t_e = \text{Time taken for 'Nr' revolutions} \quad (seconds)$$

T
TABULATION :

S.No	Delivery pressure reading Pd kg / cm ²	Suction pressure reading Ps mm of Hg	Delivery head Hd = Pdx12.5 m	Suction head Hs = Ps x 0.0136 m	Datum head Z m	Total head H m	Time taken for 10 cm of rise of water in tank t sec	Actual discharge Q _{act} m ³ /s	Time taken for N rev of energy meter disc t sec	Input power Pi kw	Output power Po kw	η %
Mean =												

4. OUTPUT POWER:

Where,

$$P_o = W \times Q_{act} \times H / 1000 \quad (\text{watts})$$
$$W = \text{Specific weight of oil} \quad (\text{N} / \text{m}^3)$$
$$Q_{act} = \text{Actual discharge} \quad (\text{m}^3 / \text{s})$$
$$h = \text{Total head of oil} \quad (\text{m})$$

5. EFFICIENCY:

$$\eta\% = (\text{Output power } P_o / \text{input power } P_i) \times 100$$

DESCRIPTION:

The gear oil pump consists of two identical intermeshing spur wheels working with a fine clearance inside the casing. The wheels are so designed that they form a fluid tight joint at the point of contact. One of the wheels is keyed to driving shaft and the other revolves as the driven wheel.

The pump is first filled with the oil before it starts. As the gear rotates, the oil is trapped in between their teeth and is flown to the discharge end round the casing. The rotating gears build-up sufficient pressure to force the oil in to the delivery pipe.

PROCEDURE:

1. The gear oil pump is started.
2. The delivery gauge reading is adjusted for the required value.
3. The corresponding suction gauge reading is noted.
4. The time taken for 'N' revolutions in the energy meter is noted with the help of a stopwatch.
5. The time taken for 'h' rise in oil level is also noted down after closing the gate valve.
6. With the help of the meter scale the distance between the suction and delivery gauge is noted.
7. For calculating the area of the collecting tank its dimensions are noted down.
8. The experiment is repeated for different delivery gauge readings.
9. Finally the readings are tabulated.

GRAPH:

1. Actual discharge Vs Total head
2. Actual discharge Vs Efficiency
3. Actual discharge Vs Input power
4. Actual discharge Vs Output power

MODEL CALCULATION:

RESULT:

Thus the performance characteristic of gear oil pump was studied and maximum efficiency was found to be..... %.

Conducting experiments and drawing the characteristic curves of Jet Pump

AIM:

To study the performance characteristics of a Jet pump and to determine the characteristic with maximum efficiency.

APPARATUS REQUIRED:

1. Jet pump setup
2. Meter scale
3. Stop watch

FORMULAE:

1. ACTUAL DISCHARGE:

$$Q_{act} = A \times y / t \quad (\text{m}^3 / \text{s})$$

Where:

A = Area of the collecting tank (m²)

y = 10 cm rise of water level in the collecting tank

t = Time taken for 10 cm rise of water level in collecting tank.

2. TOTAL HEAD:

$$H = H_d + H_s + Z$$

Where:

H_d = Discharge head, meter

H_s = Suction head, meter

Z = Datum head, meter

3. INPUT POWER:

$$I/P = (3600 \times N \times 1000) / (E \times T) \text{ (watts)}$$

Where:

N = Number of revolutions of energy meter disc

E = Energy meter constant (rev / Kw hr)

T = time taken for 'Nr' revolutions (seconds)

4. OUTPUT POWER:

$$P_o = \rho \times g \times Q \times H / 1000 \quad (\text{watts})$$

Where,

$$\rho = \text{Density of water} \quad (\text{kg} / \text{m}^3)$$

$$g = \text{Acceleration due to gravity} \quad (\text{m} / \text{s}^2)$$

$$H = \text{Total head of water} \quad (\text{m})$$

5. EFFICIENCY:

$$\eta_o = (\text{Output power o/p} / \text{input power I/p}) \times 100 \%$$

Where,

$$O/p = \text{Output power kW}$$

$$I/p = \text{Input power} \quad \text{kW}$$

DESCRIPTION:

Jet pumps are combination of conventional water pump (centrifugal or turbine pump) and an ejector. This ejector or reducer is called jet. The jet is placed within suction distance of the water which is limited to 4.6 to 6m. The function of jet is to lift the water from source to within the suction distance.

PROCEDURE:

1. Prime the pump and switch on the unit
2. Open the delivery valve and maintain the required delivery head
3. Note down the reading and note the corresponding suction head reading
4. Close the drain valve and note down the time taken for 10 cm rise of water level in collecting tank
5. Measure the area of collecting tank
6. For different delivery pressure, repeat the experiment
7. For every set reading note down the time taken for 5 revolutions of energy meter disc.

GRAPHS:

1. Actual discharge Vs Total head
2. Actual discharge Vs Efficiency
3. Actual discharge Vs Input power
4. Actual discharge Vs Output power

MODEL CALCULATION:

RESULT:

Thus the performance characteristics of jet pump was studied and the maximum efficiency was found and the characteristics curves are drawn.

Conducting experiments and drawing the characteristic curves of Kaplan Turbine

AIM

To conduct experiments and draw the characteristic curves of Kaplan Turbine

APPARATUS REQUIRED:

1. Orifice meter
2. Stopwatch
3. Tachometer
4. Dead weight

FORMULAE:

1. MANOMETER READING:

$$h = (h_1 - h_2) \times 12.6 \text{ m}$$

2. DISCHARGE FROM ORIFICE:

$$Q = 0.6 \left(\frac{a_1 a_2 \sqrt{2gh}}{\sqrt{a_1^2 - a_2^2}} \right) \text{ m}^3/\text{s}$$

d_1 = Diameter of inlet pipe = 0.13 m

d_2 = Diameter of orificemeter = 0.1 m

a_1 & $a_2 = \pi r^2$

3. INPUT POWER:

$$P_i = H Q \rho_w g \text{ watts}$$

Where,

H = Head of water on turbine in meters of water column
(pressure gauge reading – vacuum gauge reading)

Q = Effective diameter of brake drum = 0.315 m

ρ_w = Density of water (Kg/m³)

g = gravitational constant

4. OUTPUT POWER:

$$P_o = 2\pi NT/60 \text{ kW}$$

Where,

N = Speed in rpm

T is Torque = Radius of drum * $(T_1 - T_2)$ * g

5. EFFICIENCY:

$$\eta = (P_o / P_i) \times 100$$

DESCRIPTION:

Kaplan turbine is an axial flow reaction turbine used in dams and reservoirs of low height to convert hydraulic energy into mechanical and electrical energy. They are best suited for low heads say from 10m to 5 m. the specific speed ranges from 200 to 1000

The flow through the pipelines into the turbine is measured with the orifice meter fitted in the pipeline. A mercury manometer is used to measure the pressure difference across the orifice meter. The net pressure difference across the turbine output torque is measured with a pressure gauge and vacuum gauge. The turbine output torque is determined with the rope brake drum. A tachometer is used to measure the rpm.

EXPERIMENTAL PROCEDURE:

1. Keep the runner vane at require opening
2. Keep the guide vanes at required opening
3. Prime the pump if necessary
4. Close the main sluice valve and they start the pump.
5. Open the sluice valve for the required discharge when the pump motor switches from star to delta mode.
6. Load the turbine by adding weights in the weight hanger. Open the brake drum cooling water gate valve for cooling the brake drum.
7. Measure the turbine rpm with tachometer
8. Note the pressure gauge and vacuum gauge readings
9. Note the orifice meter pressure readings.

Repeat the experiments for other loads

GRAPHS:

The following graphs are drawn.

1. BHP Vs IHP
2. BHP Vs speed
3. BHP Vs Efficiency

MODEL CALCULATION:

RESULT:

Thus the performance characteristic of the Kaplan Turbine is done and the maximum efficiency of the turbine is.....%

Study on performance characteristics of Pelton turbine

AIM:

To conduct load test on pelton wheel turbine and to study the characteristics of pelton wheel turbine.

APPARATUS REQUIRED:

1. Venturimeter
2. Stopwatch
3. Tachometer
4. Dead weight

FORMULAE:

1. VENTURIMETER READING:

$$h = (P1 - P2) \times 10 \quad (\text{m of water})$$

Where,
P1, P2 - Venturimeter reading in Kg /cm²

2. DISCHARGE:

$$Q = 0.0055 \times \sqrt{h} \quad (\text{m}^3 / \text{s})$$

3. BRAKE HORSE POWER:

$$\text{BHP} = (\pi \times D \times N \times T) / (60 \times 75) \quad (\text{hp})$$

Where,
N = Speed of the turbine in (rpm)
D = Effective diameter of brake drum = 0.315 m
T = Torsion in To + T1 - T2 (Kg)

4. INDICATED HORSE POWER:

$$\text{IHP} = (1000 \times Q \times H) / 75 \quad (\text{hp})$$

Where,
H = Total head (m)

5. PERCENTAGE EFFICIENCY:

$$\% \eta = (\text{B.H.P} / \text{I.H.P} \times 100) \quad (\%)$$

S.No	Pressure Gauge Reading [Hp] Kg\cm ²	Total Head [H] m of water	Venturimeter reading Kg/cm ²		H = (P1-P2) x 10 m of water	Weight of hanger To Kg	Speed of turbine N Rpm	Weigh of hanger [T1] kg	Spring Balance T2 Kg	Tension [T] Kg	Discharge Q x10 ⁻³ m ³ /sec	B.H.P hp	I.H.P hp	η %
			P1	P2										
Mean =														

DESCRIPTION:

Pelton wheel turbine is an impulse turbine, which is used to act on high loads and for generating electricity. All the available heads are classified in to velocity energy by means of spear and nozzle arrangement. Position of the jet strikes the knife-edge of the buckets with least relative resistances and shocks. While passing along the buckets the velocity of the water is reduced and hence an impulse force is supplied to the cups which in turn are moved and hence shaft is rotated.

PROCEDURE:

1. The Pelton wheel turbine is started.
2. All the weight in the hanger is removed.
3. The pressure gauge reading is noted down and it is to be maintained constant for different loads.
4. The Venturimeter readings are noted down.
5. The spring balance reading and speed of the turbine are also noted down.
6. A 5Kg load is put on the hanger, similarly all the corresponding readings are noted down.
7. The experiment is repeated for different loads and the readings are tabulated.

GRAPHS:

The following graphs are drawn.

1. BHP Vs IHP
2. BHP Vs speed
3. BHP Vs Efficiency

MODEL CALCULATION:

RESULT:

Thus the performance characteristic of the Pelton Wheel Turbine is done and the maximum efficiency of the turbine is.....%

VIVA QUESTIONS

1. What are fluid machines or Hydraulic machines?
2. How are fluid machines classified?
3. What are called turbines?
4. What is known as Euler's equation for turbo-machines?
5. Define Gross Head of a turbine.
6. Define Net head of a turbine.

Study on performance characteristics of Francis turbine

AIM:

To conduct load test on Francis turbine and to study the characteristics of Francis turbine.

APPARATUS REQUIRED:

1. Stop watch
2. Tachometer

FORMULAE:

1. VENTURIMETER READING:

$$h = (p_1 - p_2) \times 10 \quad (\text{m})$$

Where

P₁, P₂- Venturimeter readings in kg /cm²

2. DISCHARGE:

$$Q = 0.011 \times \sqrt{h} \quad (\text{m}^3 / \text{s})$$

3. BRAKE HORSEPOWER:

$$\text{BHP} = \pi \times D \times N \times T / 60 \times 75 \quad (\text{hp})$$

Where

N = Speed of turbine in (rpm)

D = Effective diameter of brake drum = 0.315 m

T = torsion in [kg]

4. INDICATED HORSEPOWER:

$$\text{HP} = 1000 \times Q \times H / 75 \quad (\text{hp})$$

Where

H = Total head in (m)

5. PERCENTAGE EFFICIENCY:

$$\% \eta = \text{B.H.P} \times 100 / \text{I.H.P} (\%)$$

S.No	Pressure Gauge Reading [Hp] Kg/cm ²		Total Head [H] m of water	Venturimeter reading Kg/cm ²		H = (P1-P2) x 10 m of water	Weight of hanger To Kg	Speed of turbine N Rpm	Weigh of hanger [T1] kg	Spring Balance T2 Kg	Tension [T] Kg	Discharge Q x10 ⁻³ m ³ /sec	B.H.P hp	I.H.P hp	η %
	H1	H2		P1	P2										
Mean =															

DESCRIPTION:

Modern Francis turbine is an inward mixed flow reaction turbine it is a medium head turbine. Hence it required medium quantity of water. The water under pressure from the penstock enters the squirrel casing. The casing completely surrounds the series of fixed vanes. The guides' vanes direct the water on to the runner. The water enters the runner of the turbine in the radial direction at outlet and leaves in the axial direction at the inlet of the runner. Thus it is a mixed flow turbine.

PROCEDURE:

1. The Francis turbine is started
2. All the weights in the hanger are removed
3. The pressure gauge reading is noted down and this is to be
Maintained constant for different loads
4. Pressure gauge reading is ascended down
5. The Venturimeter reading and speed of turbine are noted down
6. The experiment is repeated for different loads and the readings are tabulated.

GRAPHS:

The following graphs are drawn

1. BHP (vs.) IHP
2. BHP (vs.) speed
3. BHP (vs.) % efficiency

MODEL CALCULATION:

RESULT:

Thus the performance characteristic of the Francis wheel turbine is done and the maximum efficiency of the turbine is.....%